

**Ceramic
 PTC Device**

Cuboid thermistors

Shanghai Wayon Thermo/Electro Materials Co.,Ltd.

15, Lane 1750, Donggao Road, Shanghai 201208, P. R. China

Tel: 86-21- 58652154 58995165

Fax: 86-21-58651424

E-mail: market@way-on.com

[Http://www.way-on.com](http://www.way-on.com)



SCG-3R0-381BTP

Features

- Cuboid devices
- Rapid resuming
- Better stability
- Great current impact endurance


Typical Applications

- Automobile air conditioning
- Direct current power supplies
- Heater



Product Dimensions (mm)

Part number	A mm	B mm	C mm
SCG-3R0-381BTP	30.0	30.0	2.2



Marking system

SCG-Product family
3R0- Resistance Value

Electrical Characteristics

Part number	R(25) ()	V _{max} (V _{Ac})	I _H (A)	I _T (A)	I _{max} (A)	T _f ()
SCG-3R0-381BTP	3.0 ± 20%	380	0.85	1.7	8.0	80

R(25)=Device resistance at 25 .

V_{max}=Maximum voltage device can withstand without damage at rated current.

I_H=Hold current: maximum current at which the device will not trip at 25 still air.

I_T=Trip current: minimum current at which the device will always trip at 25 still air.

T_f=Curie point.

Package Information

Bulk: 200pcs per bag.